



TS4.224 Size 2-4 Architectural Slimline Overhead Door Closer

Product Overview:

A stylish adjustable power overhead door closer, which is suitable for many applications where there is general usage, such as office accommodation, flat entrance doors etc.

4 8 3 1 1 3

Testing & Standards:

- CE marked against EN1154
- Included in successful fire test to EN1634
- Certifire approved - refer to CF689 for scope of approval
- Safe in use
- High corrosion resistance

Specification

Closing Force (Fig 1 & Fig 6)	EN Size	3**
Door Size (max)	Width (mm)	950
	Weight (kg)	60
Body Dimensions	Length (mm)	220
	Width (mm)	52
	Depth(mm)	42
Application	Regular Fig. 1	y
	Parallel Arm Fig. 6	y
	Transom Fig. 61	y*
Mechanism	Rack & Pinion	y
Power Shoe Bracket		y
Angle Of Opening		180 ⁰
Non Handed		y
Power Adjustment By Spring		n
Power Adjustment By Position		y
Adjustable Sweep Speed		y
Adjustable Latch Speed		y
Adjustable Backcheck		o*
Adjustable delayed Action		n
Guarantee	Years	25

Options

Architave Brackets	n
Drop Plates	n
Hold-Open Arm (not suitable for use on fire doors)	y*
Slide Arm & Track	y*
Hollow Door Fixing Pack	y*
Saddle Bracket For Glass Door Installation	n

Cover Options

Radius Edge	y
Semi-Radius	n
Full-Radius	n
Square	n

Finish Options

No Cover	SIL
Cover	SIL, SSS, PSS, PB, RAL, BRONZE

** optional 2-4 by template (not covered by Certifire approval)

* these options are not covered by the Certifire approval