

DESCRIPTION

Johnstone's Satin Finish is a solvent-based mid sheen finish formulated for interior use on wood and metalwork. A hard wearing, washable coating which is easy to use, it provides long term protection to doors and radiators.

RECOMMENDED USES

INTERIOR

Suitable for interior use.



TYPE OF SUBSTRATE

Wood and metal.

COLOUR RANGE

Brilliant White.

FINISH

Satin.

VOLUME SOLID

61%

COVERAGE

COVERAGE

18-20

M²/LITRE

Approximately 18-20 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME*

RECOAT

16-24

HRS

Recoat after 16-24 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

White spirit.

VOC CONTENT

High VOC content 25-50% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC.

FILM THICKNESS

Wet: 50µm, dry: 31µm.

KEY PROPERTIES

- A hard wearing solvent-based mid sheen finish.
- Washable.
- For interior use on wood and metal.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Prime bare surfaces with the appropriate primer. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION

APPLICATION METHOD



Stir well. Easy to apply by brush.

CLEANING

CLEAN IN WHITE SPIRIT



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- FLAMMABLE
- Contains 2-butanone oxime.
- May produce an allergic reaction.
- Keep away from sources of ignition - No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner - DO NOT USE SOLVENT OR THINNERS.
- Restrict interior use to small surface areas such as doors, window frames and skirting boards. Not recommended for interior use on large surface areas - walls, floors or ceilings - or in confined spaces.
- If swallowed seek medical advice immediately and show this container or label.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

SIZES

1 Litre, 2.5 Litre.