

## DESCRIPTION

Johnstone's Jonmat is a premium quality contract matt emulsion formulated for interior use on walls and ceilings. It provides an obliterating, permeable finish that is ideal for new plaster.

## RECOMMENDED USES



Suitable for interior use.

## TYPE OF SUBSTRATE

New plaster. Also suitable for use on aged plaster, wall boards, concrete, cement rendering, brickwork and blockwork in internal situations.

## COLOUR RANGE

Over 7,000 colours are available via the Johnstone's Tinting System.

## FINISH

Matt.

## VOLUME SOLID

23%

## COVERAGE



Approximately 12–14 square metres per litre, depending on the nature and porosity of the surface.

## DRYING TIME



Touch dry in 1–2 hours.  
Recoat after 2–4 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

## THINNER

Clean water.

## VOC CONTENT

Minimal VOC content 0.3–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010).  
This product contains max 3g/l VOC.

## FILM THICKNESS

Wet: 90µm, dry: 21µm.

## KEY PROPERTIES

- A premium obliterating matt contract emulsion for interior use.
- Specially formulated for use on new plaster allowing the substrate to breathe.
- Combines quality and economy.
- EU Ecolabel accredited

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354354.

## APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces such as new plaster with a coat of Jonmat thinned up to 20% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

## SIZES

5 Litre, 10 Litre, 15 Litre.